





	SoundStation IP 5000	SoundStation Duo	SoundStation IP 6000	SoundStation IP 7000
				
	Advanced IP conference phone with HD Voice clarity, designed for small conference rooms and executive offices	Most versatile, dual-mode analog and IP conference phone for small to midsize rooms	Next-generation IP conference phone designed for small to midsize rooms	Astounding voice quality and clarity from the worlds most advanced IP conference phone.
Network Connectivity				
Analog		.		
Digital PBX				
SIP VoIP
Voice Quality				
Polycom HD Voice technology	. HDvoice	. HDvoice	. HDvoice	. HDvoice
Loudspeaker Frequency	250Hz - 7kHz	220Hz - 7kHz	220Hz - 14kHz	160Hz - 22kHz
Microphone pickup range	2.5m/7ft	3m/10ft	4m/12ft	6m/20ft
Intelligent Microphone Mixing
Dynamic Noise Reduction
Automatic Gain Control
Optional expansion microphones		.	.	.
Additional Features				
Resists interference from wireless devices
Software upgradable
Mobile phone and computer connectivity		.		.
Large display to support advanced applications				.
Polycom Video Integration				.
Multi-unit connectivity				.(3)
Connect to external audio system				.(3)
Bluetooth connectivity				






Polycom Conference Phone Pocket Guide

	2200-30900-xxx SoundStation IP 5000 (SIP) conference phone. 802.3af Power over Ethernet. Includes 25' (6 meter) Cat5 shielded Ethernet cable	PN 2200-19000-xxx SoundStation Duo conference phone. AC power or 802.3af Power over Ethernet. Includes universal power supply and 7ft (2.1m) Cat5 shielded Ethernet cable.	2200-15600-xxx SoundStation IP 6000 (SIP) conference phone. 802.3af Power over Ethernet. Expandable. Includes 25' (6 meter) Cat5 shielded Ethernet cable.	
1) Models available with integration to selected digital PBX. See product details for more information 2) Available on selected models 3) Optional accessory required			2200-15660-xxx SoundStation IP 6000 (SIP) conference phone. AC power or 802.3af Power over Ethernet. Includes 100-240V power supply, 0.4A, 48V/19W; 25 ft/6m Cat5 shielded Ethernet cable; Pwr Insert Cable. Expandable.	2230-40300-xxx SoundStation IP 7000 (SIP) conference phone. AC power or 802.3af Power over Ethernet. Includes 100-240V power supply, 1.5A, 48V/50W; 25ft/6m Cat5 shielded Ethernet cable; Power Insertion Cable. Expandable.
				2230-40500-xxx SoundStation IP 7000 multi unit connectivity kit. For large room coverage. Includes two IP 7000 consoles, multi-interface module with universal power supply, console interconnect cable.



 Microphone pickup range

 Microphone pickup range with additional Microphones



	SoundStation® VTX 1000 	SoundStation2™ 	SoundStation Duo™ 	SoundStation2W™ 	VoiceStation® 500 	VoiceStation® 300 
	High-performance conference phone for remarkable voice quality in larger conference	Business-quality conferencing for small to medium offices	Most versatile, dual-mode analog and IP conference phone for small to midsize rooms	Wireless freedom to conference anywhere even where there are no phone lines	Designed for offices and small meeting spaces, with Bluetooth available	Designed for offices and small meeting spaces
Network Connectivity						
Analog	•	•	•	•	•	•
Digital PBX		• (1)				
SIP VoIP			•			
Voice Quality						
Polycom HD Voice technology						
Loudspeaker Frequency	80Hz - 7kHz	300Hz - 3300Hz	220Hz - 7kHz	300Hz-3500Hz	300Hz-3300Hz	300Hz - 3300Hz
Microphone pickup range	6m/20ft	3m/10ft	3m/10ft	3m/10ft	2m/7ft	2m/7ft
Intelligent Microphone Mixing	•	•	•	•	•	•
Dynamic Noise Reduction	•	•	•	•	•	•
Automatic Gain Control	•		•			
Optional expansion microphones	•	•	•	•		
Additional Features						
Resists interference from wireless devices	•	•	•	•	•	•
Software upgradable	•		•	•		
Mobile phone and computer connectivity		• (2)	•	•	•	
Large display to support advanced applications						
Polycom Video Integration	•					
Multi-unit connectivity						
Connect to external audio system	•	•		•		
Bluetooth connectivity					•	

	2200-07142-xxx SoundStation VTX 1000 (EX Mics Included)	2200-15100-xxx SoundStation2 conference phone, nonexpandable, w/o display	PN 2200-19000-xxx SoundStation Duo conference phone, AC power or 802.3af Power over Ethernet. Includes universal power supply and 7ft (2.1m) Cat5 shielded Ethernet cable.	2200-07800-xxx SoundStation2W (Expandable) 1.9 GHz DECT Wireless, 24 hour talk time battery, Expandable with 2 EX mics (sold as accessory), Secure voice encryption, Cell phone connection	2200-17900-xxx VoiceStation 500 analog conference phone for small rooms and offices. High quality, standard analog connection plus computer or mobile phone calls via Bluetooth or wired mode	2200-17910-xxx VoiceStation 300 analog conference phone for small rooms and offices
	2200-07300-xxx SoundStation VTX 1000 (w/o Ex Mics and Subwoofer)- fully auto conference phone featuring VTX Wideband Voice and Auto Gain Control, does not include Subwoofer and Ex Mics	2200-16000-xxx SoundStation2 conference phone, non-expandable, w/display		2200-07880-xxx SoundStation2W (Basic) 1.9 GHz DECT Wireless, 12 hour talk time battery, Secure voice encryption, Cell phone connection		
	2200-07500-xxx SoundStation VTX 1000 (EX Mics Not Included)	2200-16200-xxx SoundStation2 conference phone, expandable, w/display			1) Models available with integration to selected digital PBX. See product details for more information 2) Available on selected models 3) Optional accessory required	

 Microphone pickup range
 Microphone pickup range with additional Microphones

